

3m s10 projector user manual



File Name: 3m s10 projector user manual.pdf

Size: 2892 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 21 May 2019, 21:20 PM

Rating: 4.6/5 from 668 votes.

Status: AVAILABLE

Last checked: 19 Minutes ago!

In order to read or download 3m s10 projector user manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with 3m s10 projector user manual . To get started finding 3m s10 projector user manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

3m s10 projector user manual

The internal 3LCD technology is an innovative 3chip design that sets itself apart by delivering vibrant, true-to-life images with better color brightness and a wider color gamut. Ideal for the office and home use. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners. After reading, store them in a safe place for future reference. Little space is required for installation and large images can easily be realized. Ultra High Brightness Crisp, ultrabright presentations is achieved by using a UHB ultra high brightness lamp and a highly efficient optical system. VIDEO button rgb, video, svideo and component video. Refer to the illustrations and tables below to determine the screen size and projection distance. To prevent damaging the projector and injuring yourself, ALWAYS HOLD THE PROJECTOR whenever using the elevator buttons to adjust the elevator feet. See the rear of the projector. You can see the ports. Connecting to a computer RGB out RGB cable Dsub 15 pin video L audio R Audio out Audio cable Stereo mini audio. Doing so may result in malfunction. Please power on the projector before the connected devices. When the button is pressed, the projector switches to the rgb port. Please power on the projector before the connected devices. Power off the projector after the connected devices. Press the button of the projector or the remote control. ASPECT AUTO BLANK VOLUME VOLUME MAGNIFY VOLUME MUTE FREEZE KEYSTONE Use the buttons to adjust the. MAGNIFY MAGNIFY The projector enters MAGNIFY mode. Press the POSITION button again FREEZE KEYSTONE to finalize the zoom area. Cycle through input signals, displaying the images of retrieved signals. ASPECT AUTO BLANK video svideo. Each of these menus is operated using the same methods. Performing the SAVE1, SAVE2, SAVE3 or SAVE4 puts the current setting data MY MEMORY on the memory whose number corresponds. <http://emachn.com/userfiles/comcast-cable-box-remote-manual.xml>

- **3m s10 projector manual, 3m s10 projector user manual, 3m s10 projector user manual pdf, 3m s10 projector user manual download, 3m s10 projector user manual 2017, 3m s10 projector user manual free.**

OPTION Perform each operation in accordance with the instructions in the SELECT. At a VIDEO input of NTSC 3.58, this function performs only when the TURN OFF is VIDEO NR selected under the 3DYCS. OPTION Perform each operation in accordance with the instructions in the SELECT table below. OPTION Perform each operation in accordance with the instructions in the SELECT table below. OPTION Perform each operation in accordance with the instructions in the table below. SELECT Item Description. The lamp can break with a loud bang, or burn out, if jolted or scratched, handled while hot, or worn over time. Note that each lamp has a different lifetime, and some may burst or burn out soon after you start using them. The air filter may be attached when you buy a replacement lamp for this projector. Please replace the air filter as soon as possible. Turn off the projector, and unplug the power cord. Contact your local dealer to prepare a Filter cover new air filter. When any such message is displayed on the screen, please respond as described below. If the same message is displayed after the treatment, or if a message other than the following appears, please contact your dealer or service company. CLEAN THE AIR FILTER Please immediately turn the power OFF, and clean or change POWER OFF FIRST, the air filter by referring to the "Air Filter" section of this manual. In such a case, press the " " power OFF side of the main power switch, and wait at least 45 minutes. Turn the power OFF and wait at least 20 minutes. After the unit has sufficiently cooled down, Lighting or Blinking in please make confirmation of the following item, and then blinking in Turned off. Never use the projector if abnormal operations such as smoke, strange

odor, excessive sound, damaged casing or elements or cables, penetration of liquids or foreign matter, etc. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners. <http://gdctogo.com/mae/mm/comcast-box-manuals.xml>

After reading, store them in a safe place for future reference. 1 S10 Multimedia Projector Operator's Guide 01S10En 03.9.24 507 PM 1 Ask your question here. Provide a clear and comprehensive description of the issue and your question. The more detail you provide for your issue and question, the easier it will be for other 3M S10 owners to properly answer your question. Ask a question About the 3M S10 This manual comes under the category Video projectors and has been rated by 1 people with an average of a 5.8. This manual is available in the following languages English. Do you have a question about the 3M S10 or do you need help. Ask your question here 3M S10 specifications Brand ManualSearcher.com ensures that you will find the manual you are looking for in no time. Our database contains more than 1 million PDF manuals from more than 10,000 brands. Every day we add the latest manuals so that you will always find the product you are looking for. Its very simple just type the brand name and the type of product in the search bar and you can instantly view the manual of your choice online for free. ManualSearcher. com If you continue to use this site we will assume that you are happy with it. Read more Ok. After reading, store them in a safe place for future reference. AUTO button ports of video, svideo executes automatic and component video. adjustment. ASPECT button BLANK button toggles between the blanks the screen modes for aspect ratio. You can use the elevator feet to make adjustments if the surface on which you need to set the projector is uneven or if you see the rear of the projector. You can see the ports. Please power on the projector before the connected devices. MAGNIFY VOLUME ON As illustrated below, each time you press the button, the projector switches be Power off the projector after the connected devices. Press the button of the projector or 1 the remote control.

The projector lamp will go off, and the power power indicat ESC RESET Even if you dont do anything, the dialog will automatically disappear after When you want to initialize the position, press the RESET button during adjustment. Press the POSITION button again to close the dialog and co Dark pictures may still be incorrec Press the POSITION button again FREEZE KEYSTONE to finalize the zoom area. POSITION POSITION POSITION MENU ENTER ESC RESET, Use the buttons to adjust the zoom 3 level. Press the MAGNIFY OFF button to exit. All other trademarks are the property of their respective owners. After reading, store them in a safe place for future reference. 1 S10 Multimedia Projector Operator's Guide 01S10En 03.9.24 507 PM 1 1 2 3. 45 Summary of content 45 pages Page 1 01S10En 03.9.24 507 PM 1 S10 Multimedia Projector Operator's Guide Thank you for purchasing this projector. After reading, store them in a safe place for future reference. Little space is required for installation and large images can easily be realized. Ultra High Brightness Crisp, ultrabright presentations is achieved by using a UHB ultra high brightness lamp and a highly efficient optical system. Page 6 01S10En 03.9.24 507 PM 6 Part Names continued The Remote Control RGB button 21 15 selects the input signal of rgb port. VIDEO button 15 toggles between the signal ports of video, svideo and component video. Refer to the illustrations and tables below to determine the screen size and projection distance. To prevent damaging the projector and injuring yourself, ALWAYS HOLD THE PROJECTOR whenever using the elevator buttons to adjust the elevator feet. Page 10 01S10En 03.9.24 507 PM 10 Setting Up continued Please refer to the following for connecting your devices. See the rear of the projector. If it is damaged, contact your dealer to newly get correct one. Page 12 01S10En 03.9.24 507 PM 12 Remote Control Putting Batteries CAUTION Always handle the batteries with care and use them only as directed.

<http://www.drupalitalia.org/node/68143>

Do not mix new batteries with used ones. Do not look into the lens or vents of the projector. Please power on the projector before the connected devices. Please power on the projector before the

connected devices. Power off the projector after the connected devices. 1 Press the button of the projector or the remote control. VOLUME As illustrated on the right, a dialog will appear on the screen to aid you in adjusting the volume. As illustrated on the right, a dialog will appear on the screen to aid you in adjusting the position. BLANK VOLUME MAGNIFY ON MUTE POSITION OFF FREEZE KEYSTONE POSITION POSITION MENU ENTER ESC RESET 2, Use the the position.,, buttons to adjust When you want to initialize the position, press the RESET button during adjustment. Page 19 01S10En 03.9.24 507 PM 19 Operating continued Using The Automatic Adjustment Feature 1 Press the AUTO button. Make sure that the application window is set to its maximum size prior to attempting to use this feature. Page 20 01S10En 03.9.24 507 PM 20 Operating continued Using The Magnify Feature 1 Press the MAGNIFY ON button. 2 Press the POSITION button, then use the,, buttons to select the area to zoom. Press the POSITION button again to finalize the zoom area. SEARCH AUTO BLANK VOLUME MAGNIFY ON MUTE OFF FREEZE KEYSTONE POSITION POSITION POSITION MENU ENTER ESC RESET 3 Use the level. Cycle through input signals, displaying the images of retrieved signals. If no signal is found, returns to the signal that was selected before the search was begun. Page 22 01S10En 03.9.24 507 PM 22 Multifunctional Settings Using The Menu Functions This projector has the following menus MAIN, PICTURE1, PICTURE2, INPUT, AUTO, SCREEN, OPTION. Each of these menus is operated using the same methods. Page 23 01S10En 03.9.24 507 PM 23 Multifunctional Settings continued MAIN Menu With the MAIN menu, the items shown in the table below can be performed. Perform each operation in accordance with the instructions in the table below.

<http://www.friendshiptransport.net/images/canon-lc-2050p-manual.pdf>

Page 24 01S10En 03.9.24 507 PM 24 Multifunctional Settings continued PICTURE 1 Menu With the PICTURE 1 menu, the items shown in the Table below can be performed. Performing the SAVE1, SAVE2, SAVE3 or SAVE4 puts the current setting data on the memory whose number corresponds. Page 26 01S10En 03.9.24 507 PM 26 Multifunctional Settings continued PICTURE 2 Menu With the PICTURE 2 menu, the items shown in the table below can be performed. Item V POSITION H POSITION H PHASE H SIZE OVER SCAN RESET 20 142 31 1344 95 SELECT Description V POSITION Adjust the Vertical Position Up. Page 27 01S10En 03.9.24 507 PM 27 Multifunctional Settings continued INPUT Menu With the INPUT menu, the items shown in the table below can be performed. Page 28 01S10En 03.9.24 507 PM 28 Multifunctional Settings continued INPUT Menu continued Description VIDEO NR Select a Noise Reduction Mode HIGH. Page 29 01S10En 03.9.24 507 PM 29 Multifunctional Settings continued AUTO Menu With the AUTO menu, the items shown in the table below can be performed. MENU MAIN PICTURE1 PICTURE2 INPUT AUTO SCREEN OPTION ADJUST POWER OFF SEARCH RESET 0 min TURN ON SELECT Item Description ADJUST Automatically Adjust the Picture Pressing the or the ENTER button performs this function. Page 30 01S10En 03.9.24 507 PM 30 Multifunctional Settings continued SCREEN Menu With the SCREEN menu, the items shown in the table below can be performed. Page 31 01S10En 03.9.24 507 PM 31 Multifunctional Settings continued OPTION Menu With the OPTION menu, the items shown in the table below can be performed. Page 32 01S10En 03.9.24 507 PM 32 Lamp WARNING HIGH VOLTAGE HIGH TEMPERATURE HIGH PRESSURE The projector uses a highpressure mercury glass lamp. The lamp can break with a loud bang, or burn out, if jolted or scratched, handled while hot, or worn over time. Note that each lamp has a different lifetime, and some may burst or burn out soon after you start using them.

<http://intrasservices.com/images/canon-lbp-5050-instruction-manual.pdf>

The air filter may be attached when you buy a replacement lamp for this projector. Please ask your dealer. If the indicators or a message prompts you to replace the lamp, replace the lamp as soon as possible. The use without the air filter could result in damage. Page 35 01S10En 03.9.24 507 PM 35 Air Filter continued Replacing The Air Filter If the soiling will not come off the air filter, or it

becomes damaged, then it needs to be replaced. Please replace the air filter as soon as possible. 1 Turn off the projector, and unplug the power cord. 2 Contact your local dealer to prepare a new air filter. Tell the dealer your air filter type number. 3 After making sure that the projector has cooled adequately, remove the filter cover. Page 37 01S10En 03.9.24 507 PM 37 Troubleshooting Related Messages When the units power is ON, messages such as those shown below may be displayed. When any such message is displayed on the screen, please respond as described below. If the same message is displayed after the treatment, or if a message other than the following appears, please contact your dealer or service company. Page 38 01S10En 03.9.24 507 PM 38 Troubleshooting continued Related Messages continued Message Description A note of precaution when cleaning the air filter. CLEAN THE AIR FILTER Please immediately turn the power OFF, and clean or change POWER OFF FIRST, the air filter by referring to the "Air Filter" section of this manual. In such a case, press the "0" power OFF side of the main power switch, and wait at least 45 minutes. Page 40 01S10En 03.9.24 507 PM 40 Troubleshooting continued Regarding The Indicator Lamps continued power indicator Lighting or blinking in red lamp indicator temp indicator Turned off The cooling fan is not operating. Turn the power OFF and wait at least 20 minutes. After the unit has sufficiently cooled down, Blinking in please make confirmation of the following item, and then red resent the power to ON.

Never use the projector if abnormal operations such as smoke, strange odor, excessive sound, damaged casing or elements or cables, penetration of liquids or foreign matter, etc. Change by releasing from the WHISPER mode. The 3MTM Multimedia Projectors are designed, built, and tested for use indoors, using 3M lamps, 3M ceiling mount hardware, and nominal local voltages. We delete comments that violate our policy, which we encourage you to read. Discussion threads can be closed at any time at our discretion. Please try again. You don't have to pay anything extra!! Please try your search again later. You can edit your question or post anyway. Featuring true SVGA 800 x 600 native resolution combined with a 3001 contrast ratio and 1,200 lumens of brightness, this projector is not only good looking, but it will keep you looking good whether at home or on the road. Weighing in at just 6.6 pounds, the S10 projector is fully prepared to travel. It includes multilingual setup and operating instructions as well as three power cables one each for the US, UK, and mainland Europe. In addition to being HDTV ready, the S10 accepts a wide range of input sources and signals and even offers builtin sound through a 1 watt speaker. The S10 offers manual zoom and focus control 1.21 and supports both 43 and 169 aspect ratios. Depending on the size of your venue, the S10 can project an image ranging from 30 to 300 inches diagonal with keystone correction. The S10 comes backed by a three year warranty one year on the lamp and comes complete with cables, a remote control, even a soft carrying case.

roofmed.ru/wp-content/plugins/formcraft/file-upload/server/content/files/1626be07090521---casio-4395-manual.pdf

Whats in the Box S10 projector, power cords x3 US, UK, Euro, RGB computer cable, component video cable, remote control, multilanguage Quick Start Guide, CDROM with driver and multilanguage Operators Guide, softside bag If you are a seller for this product, would you like to suggest updates through seller support Amazon calculates a products star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers and factors that establish reviewer trustworthiness. Terms of use. Excellent image quality. Lighted control panel buttons. Cons Relatively low brightness. Weak printed documentation Bottom Line 3M has made a splash with its entry into the digital data projector market. Pininfarina design combined with quality and attention to detail make this a strong competitor right out of the box. The projector could be brighter, but it should still suffice for most conference rooms. Both owe their stylish appearance to the legendary Italian design firm, Pininfarina. Click here to read the. SEE ALSO The Best Portable

Projectors for 2020 Both owe their stylish appearance to the legendary Italian design firm, Pininfarina. But its not just another pretty face The SVGAresolution LCD projector aggressively competes in the entrylevel market. One of the most impressive features is a circular base that makes aligning an image properly on a screen incredibly easy—no more fumbling with screwtype feet adjustments. Though its a little bulky for A single RGB connector handles computer connections. A serial port allows remote control of the projector, but its use is not documented in the manual. The S10 also features a full complement of video connectors. It maintained excellent focus throughout the screen and excellent gray shade response at both ends of the spectrum. Convergence was very good. There were faint, fine bars in the color ramps, but colors were good.

The S10 delivered only 813 lumens on our tests—sufficient for a moderatesize image in a room without too much ambient light. All told, the Bravo S10 has attractive styling, innovative design features, excellent image quality, and a competitive price. Please try again.Please try again.In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Projector Lamp Assembly with Osram Neolux Bulb Inside.Register a free business account Please try your search again later.MI Technologies, Inc. Next page Upload your video Video Customer Review Lutema Replacement projector lamps. See full review MI Technologies, Inc. Onsite Associates Program Amazon calculates a product's star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers, and factors that establish reviewer trustworthiness. Our payment security system encrypts your information during transmission. We don't share your credit card details with thirdparty sellers, and we don't sell your information to others. Please try again.Please try again.In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account Please try your search again later.This remote is ready to use and does not require programming, just insert 2 x AAA batteries batteries are not included and enjoy your remote. This remote certainly provides all the basic commands for your device that allows you to turn it on and off, navigate the menu and select video source and many of additional functions. Voltarea remote has a builtin laser pointer, that is a great tool for performing classes, presentations or meetings. User manual of the remote can be found on our website or by contacting us.

Amazon calculates a product's star ratings based on a machine learned model instead of a raw data average. Please see below for continued support. If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance. If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance. If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance. If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance. By continuing to browse our website, you agree to our use of cookies. For more information on how we use cookies and how to manage your preferences go to Cookie Information. PocketProjectorContentsIntended Use StatementThe ambient operating environment should be free of airborne smoke, grease,Use of this product in adverse conditions will void the product warranty. Safety Information. Please read, understand, and follow all safety information contained in theseRetain these instructions for futureExplanation of Signal Word ConsequencesTo reduce the risk associated with hazardous voltage. Use only 3Mapproved replacementThere are no userserviceable parts other than the battery. Service to beReplace damaged part priorTo reduce the risk associated with fire and explosionTo reduce the risks associated with driver distraction.

To reduce the risks associated with choking To reduce the risk associated with fire and explosion, battery leakage Use only the 3M specified To reduce the risks associated with hearing loss To reduce the risk associated with environmental contamination To reduce the risks associated with LED bright light. To reduce the risks associated with tripping and falling Safety Labels Charging Specification. Standard Charge. Cut Off Voltage LED Light Output Power 1.693 mW Introduction. Thank You For Choosing 3M. This product has been produced in accordance with 3M quality and safety Product Features. The 3M MP180 projector is an all-in-one pocket projector. It supports common. PDF, as well as standard movie and music files. Using the interchangeable microSD Storage MicroSDHC card slot capable of reading up to 32GB cards and 4 GB of Media Connects to your favorite digital media sources MP3 players, PCs, DVD Features Fully equipped with sound, 120 minutes of battery life, screen size up to Share files, photos and movies from Package Contents Table Top Tripod. Rechargeable Battery. Carrying Pouch. Outlet Adapters 4. Power Adapter. AV Adapters 3. Product Warranty and. Safety Guide. Quick Start Guide Parts. Status Indicator. Touch Screen. Remote Sensor. Focus Wheel. Lens. Speaker. Flip Stand. Tripod Socket. Battery Remote Control Using the remote control. The remote control for the 3M MP180 projector allows you control most functions The projector will begin projecting the Important Note The remote control cannot be used with the web browser, to Getting Started. Install Battery. The 3M projector comes with a rechargeable battery. The battery should be fully To install the battery point the contacts on the battery toward the contacts on the Remove Battery. To remove the battery slide the battery latch away from the battery and then lift the Important Note Use only the 3M specified battery 78697200265 Power Adapter. The power adapter is used to charge the battery or power the projector.

There Installing an Outlet Adapter onto the Power Adapter. Select the outlet adapter that will plug into your wall outlet. Align the outlet adapter to the power adapter and slide the outlet adapter into Replacing the Outlet Adapter. Push the button on the outlet adapter. Slide the outlet adapter up. Remove the outlet adapter. Charge the Battery. The 3M MP180 rechargeable battery gives you up to two hours of battery life. When the battery needs to be charged, the status indicator will turn red and begin Charge the battery by connecting the 3M MP180 power adapter to the projector. When the power adapter is connected, the battery status icon is animated while Turn the projector power off. Connect the power adapter to the projector's DC input. Connect the other end of the power adapter into the electrical outlet. The status indicator will change to amber while the battery is charging. Allow three hours to fully charge the battery. When charging is complete, the If the projector power is off, allow three hours for the battery to fully recharge. If the projector power is on, the battery will take longer to charge. The battery has a lifespan and ages every time it is fully charged and Therefore, as the battery ages the battery life will decrease. The battery cannot be charged using USB port. Battery Maintenance Tips. Remove the battery when the projector will not be used for one week or Charge and discharge the battery by turning on the projector at least once a When storing the battery for more than a month, store it at 50% charge. The Do not store a fully discharged battery because it may lose the ability to be Do not store a fully charged battery because it may lose the ability to be Making Connections. The 3M MP180 projector will display informational icons depending on the input If no devices or input cables are connected to the The 3M MP180 was designed to operate Connecting to a Composite Video Device.

Use the AV cable to input video from camcorders, digital cameras, DVD players and Connect the AV cable to the projector's VGA AV input. Connect the other end of the AV cable to the video device's audio and video Tip Some video devices do not have the standard audio and video connections The AV cable Once you have For component video input, you must purchase the optional 3M MP180 Component. AV Cable. This cable sends a higher quality video signal for the best possible image. Connect the component AV cable to the projector's VGA AV input. Connect the other end of the AV cable to the video device's audio and video Important Note There are two red connectors on the

Component AV cable. One is for the right audio channel and the other is for the Pr component video. Some video devices do not have the standard audio and video connections. The AV cable. Once you have some video devices, by default, will not output a video signal. The video. Connecting to a Computer. Use the VGA audio cable to connect the projector to desktop computers, laptop. The projector supports VGA, SVGA, XGA, and WXGA resolutions. For best results, connect the VGA cable to the 3M MP180 projector. Connect the VGA cable to the computer's video and audio outputs. Set the computer resolution to one of the supported resolutions.

Description. Resolution width x height. Refresh Rate. Powering On. Press and hold the power button for three seconds. Release the power button when. Tip The video output on some devices is turned off by default. Please refer to Powering Off. Release the power button when. The projector is off when. When the status indicator is solid amber, Status Indicator Light. The status indicator light provides information about the projector's state. Status Indicator Light. Flashes green three times. Blank. Flashes green. Solid green. Solid amber. Flashes amber. Flashes red twice and. Meaning. A new power source is connected to the projector and the projector is off.

If the power adapter is connected to the projector is starting up. The projector is on. The projector is off and charging the battery. The projector has overheated and needs to cool. The projector cannot charge the battery. The projector cannot turn on because the battery needs to be. Flashes Red. Video Mode Icons. The projector will display a video icon when it is connected to a video cable or a Touch Screen" on page 24 will display. Icon. The projector detects an NTSC video input signal. The projector detects the video input signal and displays the video. The projector detects the VGA audio cable. The projector detects computer input signal and displays the input. The projector does not support the video signal. The projector is measuring and synchronizing to video input signal. Adjusting Image Size. Image Size. Diagonal. Width. Height. Distance. Important Note As you increase the size of the projected image, you will need adjusting the focus. Turn the focus wheel to sharpen the image. Attaching the Tripod. The projector includes a tabletop tripod that mounts to the bottom of the projector. Tip The 3M MP180 projector will attach to most camera tripods. Transfer Files to Projector. The 3M MP180 projector has 4 GB of internal memory. To access the projector's. Connect the USB cable to the projector. Connect the USB cable to the computer. Turn on the projector. The projector will be detected as a removable drive labeled "3M MP180" by. Now the projector is ready to receive a file from your computer. Using the microSD Card Slot. The 3M MP180 projector has a microSD card slot that can read up to a 16 GB card. You can either place files on the card before you insert it into the projector's card. Insert microSD Card. Open the microSD slot door. Insert the microSD card into the microSD slot until it "clicks" into place. Close the microSD door. Eject microSD Card. Push the microSD card into the microSD slot until it "clicks". Release the microSD card and the card will eject.

<http://www.drupalitalia.org/node/68145>